

SYSTEM FEATURES

- Lightweight 3-axis stabilized head
- Stabilizes smaller cameras and payloads
- Designed for Cable Rigs
- HD & Ultra-HD via Fiber Optic
- Wireless control
- Fiber-Optic slip rings for HD and Ultra HD
- Rugged and lightweight
- 1 year warranty standard - all parts and labor.
- Proudly made in the U.S.A



SYSTEM SPECIFICATIONS

STABILIZATION

3-Axis Nettmann S.A.S. stabilization

GIMBAL FIELD OF VIEW

- Pan: 360 degrees continuous (360 degrees/sec)
- Tilt: 170 degrees (280 degrees/sec)
- Roll: +/-40 degrees max; steerable or auto level (40 degrees/sec)

SYSTEM ORIENTATION

Hanging only

AUTOMATIC TARGET TRACKING

Automatic/Selectable Backpan Correction

ENVIRONMENTAL

-22 to 120 Farenheit (-30 to 49 Celcius)

SYSTEM WEIGHT & SIZE

- Head Weight: 44Lbs (22kgs) - includes typical camera/lens package
- Max. Payload Weight: 15Lbs (7kgs)
- Max. Payload Size: 4.2'W x 5.5"H x 6.5"L
(10.6cm x 13.9cm x 16.1cm)

OPERATOR CONTROL DESK

Displacement Joystick



Displacement Joysticks

LENS CONTROL

Via control desk

POWER

24 VDC (72 watts stand-by, 350 watts dynamic max)